

SLIPRING Type PSP 20 - 60 A

TECHNICAL SHEET 3.4



MAIN PERFORMANCES

• HOUSING	Metallic
• POSITIONING	Vertical axis with 2 fixed screws M10
• CABLE ENTRY	Through central hole for terminal box and through two pipes union 3/4" Gas for the brush holders
• BRUSHES	20 A and 60 A in copper graphite. Slideway between rings and brushes secured by a "V" special contact
• EXECUTIONS	From 18 to 36 rings 20 A - mixed executions 20/60 A
• ARMONIZED RULES	EN 60947-5-1 EN 60529 EEC 73/23 - EEC 89/336 - EEC 89/392 Directive
• MARKING	CE

ELECTRICAL FEATURES

• NOMINAL VOLTAGE	660 V AC - DC
• NOMINAL CURRENT	Ith 20 - 60 A
• PROTECTION DEGREE	IP 42
• MAX ROTATING SPEED	30 revs/min.
• TEST VOLTAGE	2,5 kV
• OPERATING TEMPERATURE	-20 °C ÷ +60 °C

STANDARD TYPES

H = mm	Single	Mixed		TOT.
	20 A N ° rings	60 A	30 A N ° rings	
270	18	4	10	14
315	24	4	16	20
360	30	4	22	26
415	36	4	28	32

DIMENSIONS

